

Product Overview



COMPACT LASER MODULE WITHOUT COMPROMISES



KEY FEATURES:

- Output powers up to 1W
- High beam quality and stability
- Broad selection of wavelengths, fine-tunable
- Modulation up to 1.5 MHz
- Temperature-stabilized
- Long lifetime
- Software included

PowerBox laser controller



The PowerBox is a miniaturized laser controller for the Lambda Beam series of laser modules, providing power to the laser and controlling the emission and temperature. It is designed for industrial integration where small sizes and weights are important.

- Attaches directly to the Lambda Beam laser head
- Highly compact design
- Straightforward connection via screw-type terminal block
- Digital control via USB (RS-232 on request)
- Powered by 12 – 36 V DC
- Modulation input analog or digital 0 – 5 V DC
- Interlock on/off input

Alternatively, for laboratory applications and prototyping the PowerController can be used, featuring larger connectors and a keyswitch.

Full specifications for all products can be found in the datasheets available for download from our website.

*1 Multi-mode *2 Watercooler option recommended *3 on request

Type	Wave-length	Maximum output power
Diode	375 nm	20, 70, 200*1 mW
Diode	395 nm	120 mW
Diode	405 nm	75, 125, 175, 200, 300*2, 500*1*2, 1000*1,2 mW
Diode	415 nm	120 mW
Diode	420 nm	50 mW
Diode	422 nm	120 mW
Diode	430nm	50 mW
Diode	445 nm	50, 75, 100, 250*1, 500*1*2, 1000*1*2 mW
Diode	450 nm	75, 1000*1*2 mW
Diode	455nm	50, 100 mW
Diode	473 nm	100 mW
Diode	488 nm	20, 60, 200 mW
Diode	505nm	75 mW
Diode	510nm	50 mW
Diode	515 nm	25, 75 mW
Diode	520 nm	50, 120, 500*1*2 mW
DPSS	532 nm	75, 100, 125, 175, 200 mW
DPSS	532 nm	125, 175, 200 mW narrow line
Diode	633 nm	75 mW
Diode	635 nm	75, 125 mW
Diode	638 nm	75, 125, 175, 250*1, 500*1 mW
Diode	642 nm	75, 125, 175 mW
Diode	650 nm	150*1 mW
Diode	660 nm	75, 120, 175, 250*1 mW
Diode	670 nm	15, 250*1,2 mW
Diode	685 nm	40 mW
Diode	705 nm	40 mW
Diode	730 nm	40 mW
Diode	785 nm	75, 125, 200, mW
Diode	805 nm	500*1,2 mW
Diode	808 nm	75, 125, 175, 1000*1,2 mW
Diode	830 nm	45, 75, 125, 1000*1 mW
Diode	852nm	75, 125 mW
Diode	905 nm	100 mW
Diode	915 nm	75, 125, 175, 250, 1000*1*2 mW
Diode	940 nm	75, 125, 175, 200*1*2 mW
Diode	980 nm	75, 125, 175, 250, 1000*1*2 mW
Diode	1064 nm	75, 125, 175, 300*2, 500*2, 1000*1,2 mW

Lambda Beam Wavelock™

Highly stabilized compact laser system

Wavelength	Max. output power	Coherence length
405 nm	12, 25, 40 mW	> 1.0 m
633 nm	40, 70 mW	> 10.0 m
638, 640 nm	32 mW	> 1.0 m
638 nm	120 mW	> 2.0 m
658 nm	35 mW	> 1.0 m
685, 690 nm	45 mW	> 3.0 m
785 nm	80, 100 mW	> 3.0 m
785 nm	175, 225 mW	> 10.0 m
785 nm	500*1*2 mW	> 4.0 mm
785 nm	75, 100 mW	> 0.6 cm
808 nm	120 mW	> 3.0 m
830 nm	500*1*2 mW	> 4.0 mm



MINIATURIZED LASER MODULE



KEY FEATURES:


- Incredibly small yet fully featured
- Output powers up to 100 mW
- Powered via USB: no extra power adapter required
- Software included

Lambda Mini EVO

Wavelength	Maximum output power
375 nm	50 mW
405 nm	15, 50 mW
488 nm	60 mW
515 nm	25 mW
640 nm	75 mW
660 nm	75 mW
685 nm	40 mW
785 nm	75 mW
830 nm	45 mW

Lambda Mini FIBER

Wavelength	Maximum output power
405 nm	15, 50 mW
445 nm	30 mW
488 nm	20 mW *3
520 nm	25 mW *3
635 nm	30, 60 mW
660 nm	50 mW
785 nm	50 mW
808 nm	50 mW
830 nm	50 mW
1064 nm	50 mW
1310 nm	10 mW
1550 nm	10 mW




Accessories



Fiber Coupler



Shutter



Optical fiber cable

RGB Lasersystems GmbH
Donaupark 13
93309 Kelheim Germany

Tel.: +49 9441 17 50 33 - 0
sales@rgb-photonics.com
www.rgb-lasersystems.com